

Materials and Tools Needed:

- One Rejuvenation Hardware back-to-back door pull set
- Drill
- Drill bits
- Screwdriver
- Measuring tape
- Pencil
- Door marker or template (if included with the pull set)

Instructions:**1. Choose the Location:**

- Determine the ideal height for your back-to-back pull. Common placement is around 36 to 48 inches from the bottom of the door to the center of the pull. For a 24" tall pull, consider placing the center of the pull at approximately 40 inches from the bottom of the door. Adjust based on personal preference and ergonomic considerations.

2. Mark the Hole Locations:

- Holding the pull on the door in your selected location, mark the center-to-center drill holes for the pulls.

3. Drill Holes:

- With a drill, drill pilot holes at the marked center-to-center points on both sides of the door. Check the pilot holes to ensure they are located correctly according to your desired pull location and are in line on each side of the door and with each other.
- If the pilot holes are correct, with an appropriate-sized drill bit, drill through the door at each point to create the holes for the pulls.

4. Install the Pulls:

- Attach the outside pull with the supplied screws, but do not firmly secure it at this point.
- Slide the inside pull onto the screws and ensure that all is aligned correctly on the outside and inside, and there is enough length on the screw to allow the inside set screw enough length to secure the inside handle.
- If all is in order, tighten the screws and attach the inside pulls firmly with the supplied set screws.

5. Test the Door:

- Open and close the door to ensure that the back-to-back pulls function smoothly and securely.

If you're unsure or not comfortable with the installation process, consider seeking professional assistance to ensure a secure and accurate installation.